

DNS

Support TR069, NAT
DMZ, DNS features



Support Multiple SSID



Support Multiple VLAN



Support CAS, L2oGRE



Support IPV6, PPPoE, DHCP
and Static IP configuration for
WAN Interface



Support IP, MAC filtering,
- Firewall Functionality in
routed mode



Support for XPON, adaptive
EPON or GPON OLT on the
network



RL802GW-DG xPON ONT



1. Product Overview

RL802GW-DG terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators or cable operators. The box is based on the mature Gigabit GPON technology, which have high ratio of performance to price, and the technology of 802.11 n/ac WiFi, Wireless power can reach more than 23dBm, Support for USB2.0 extension devices. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And It is fully compliant with technical regulations such as ITU-T G.984.x



2. Interface of device

Parameter	Nominal
Connector style	SC/APC OR SC/UPC
PON quantity	1
Fiber style	Single mode
Wavelength	TX : 1310 +/-20nm RX : 1490 +/-10nm
PON interface standard	ITU-T G.984.2/ITU-T G.984.3/ITU-TG.988 Class B+
PON interface receiving rate	2.488Gpbs
PON interface transmitting rate	1.244Gpbs
Output optical power	Min: 0.5dBm Max: +5dBm
Optical receiver sensitivity	Precede -29dBm
The length of the optical link	Max 20km

3. WIFI Specifications

Standard	IEEE 802.11 ac/b/g/n
Frequency	2412-2472MHz
	5GHz :
	Band-1 frequency 5.15GHz ~ 5.25GHz Band-2 frequency 5.25GHz ~ 5.35GHz Band-3 frequency 5.500GHz ~ 5.700GHz Band-4 frequency 5.725GHz ~ 5.825GHz
	2.4GHz Frequency
Transmission speed	IEEE 802.11b : 11/5.5/2/1M(Auto) IEEE 802.11g : 54/48/36/24/18/12/9/6(Auto) IEEE 802.11n : 270/243/216/162/108/81/54/27Mbps, up to 300Mbps
	5GHz Frequency
	IEEE 802.11n : Highest transmission speed up to 300Mbps IEEE 802.11ac : Highest transmission speed up to 867Mbps
Channel number	2.4GHz : 13 5GHz : 4
Spread-spectrum Technique	DSSS(Direct sequence spread spectrum)
Data Modulation	DBPSK, DQPSK, CCK and OFDM(BPSK/QPSK/16-QAM/64-QAM) 270M : -68dBm@10% PER ; 130M : -68dBm@10% PER 108M : -68dBm@10% PER ; 54M : -68dBm@10% PER
Sensitivity @PER (Packet Error Rate)	11M : -85dBm@8% PER ; 6M : -88dBm@10% PER 1M : -90dBm@8% PER
Transmission Distance	Indoor Maximum 120 meter, Outdoor Maximum 360 meters (The distance depends on the environment)
RF power (2.4GHz)	20dBm EIRP
RF power (5 GHz)	Band-1 EIRP 17.45dBm
	Band-2 EIRP 17.82dBm
	Band-3 EIRP 17.92dBm
	Band-4 EIRP 18.92dBm
Antenna	5dBi Antennas

4. Specification and working environment

Parameter	Nominal
Dimension	195mm×120mm×50mm (L×W×H)
Net weight	0.3kg
Typical power consumption	<10W
Noise	None
Cooling style	Naturally cooling
Power supply	12V, 1.5Amp
Installation style	Desktop or put inside the information box
Environment	5-50°C
Atmospheric pressure	70-106Kpa
MTBF	50,000hours@25°C
MTTR	30minutes
Parameter	Nominal


5. Hardware Specification

Parameter	Nominal
WAN/PON	One Giga optical interface (SC/APC)
LAN	Two 10/100/1000 Mbps Ethernet RJ-45 ports
USB	One USB 2.0 hosts
WPS button	A tact switch
Reset	A tact switch. One reset/restore factory default button
Power button	Power on/off switch
Power supply	DC 12V/1.5A

6. Special function

- Support TR069,NAT,DMZ,DNS features
- Support Multiple ssid
- Support Multiple VLAN
- Support CAS,L2oGRE
- Support IPV6
- PPPoE
- DHCP and Static IP configuration for WAN Interface
- Support IP
- MAC filtering, Firewall Functionality in routed mode
- Support for XPON
- Adaptive EPON or GPON OLT on the network

7. Network Mode



Sold & supported by: Authorized Distributor for South India

F2TH Communications Pvt Ltd, 165, 9th Cross, Indiranagar 1st Stage, Bangalore- 560038

8197023395

sales@f2th.in

www.f2th.in